



MAXLIFE
INDUSTRIES
INNOVATING THE
BUILDING ENCLOSURE™

ArmorWall^{NP}

STRUCTURAL INSULATED SHEATHING

PRODUCT DESCRIPTION

ArmorWall interior/exterior wall sheathing is a UL Classified and tested, high strength, fire resistant exterior insulated wall sheathing product, commonly referred to as an SIS (structural insulated sheathing) panel. MaxLife's technology fuses a structural element to the exterior face of our fused insulation layer which modernizes the installation of commercial and residential wall assemblies. This innovation allows the designer to re-implement legacy design or frees them to wider creativity while maintaining wall construction speed, efficiency, and code compliance.

Amongst the factory-coated panels in the armorwall series of products, ArmorWall NP has an applied non-permeable weather resistive barrier coating. Once seam and fasteners have been sealed the envelope may be considered "dried-in" allowing interior construction to commence regardless of final exterior finish status.

PRODUCT ADVANTAGES

Fusion Technology – MaxLife's patented technology fuses component materials rather than laminating which allows for greater strength, no delamination in the field, a longer lasting product with greater weatherability. Fusion manufacturing of ArmorWall allows multiple finish veneers to be mechanically attached directly to the exterior sheathing board rather than requiring a fastener to fully penetrate the layer into the stud beyond. This allows less leakage potential and less thermal loss from fastener penetration found in traditional wall assemblies.

NFPA 285 Approved – ArmorWall (UL System No. EWS0043) allows the designer to utilize one product with multiple finish veneers and factory-coated or non-factory coated water-resistant membrane options on a single building in which all walls would be NFPA 285 compliant and approved. ArmorWall's tested traits and capabilities allow the designer more flexibility than ever seen before in the industry.

Non-Permeable – ArmorWall NP utilizes a factory-applied self-healing non-permeable air barrier membrane. ArmorWall NP is specifically designed for high humidity environments such as natatoriums or cold storage facilities.

Structural Rack & Shear – Testing by ASTM E72 demonstrates ArmorWall to be stronger than many other sheathing and wood products when attached directly to the stud with no required interior blocking.

Multi-Component Reduces Labor – ArmorWall combines multiple control layers of a wall assembly including structural, thermal, and air; into a one-step application which can be installed either vertically or horizontally. This one-step approach allows installation up to 3-5 times faster on the construction site saving time and money.

Mold & Mildew Resistant – No components exist within the product to allow any growth of mold or mildew as tested by ASTM C1338 and meet FEMA design standards for flood resistant materials.

PRODUCT LIMITATIONS

- Do not install ArmorWall NP below grade. For these applications see ArmorWall BG.
- For required NFPA 285 ratings, ArmorWall Return must be utilized at rough openings. Contact Technical Services for further details.
- Direct applied mortar/base/bond coat stucco applications require utilization of a slip sheet or drainage plane for capillary break.
- Do **NOT** use an impact drill to fasten cladding or attachments to the panel.
- Maximum stud spacing is 16" O.C. fasteners shall be placed 12" O.C. in the field. Parallel seams to studs must fall on studs and blocking is not required.

HANDLING AND USE

ArmorWall NP can be cut and installed using standard job site hand tools. When being cut to size, avoid breathing dust and minimize contact with eyes. ArmorWall NP should be stored off the ground in original shipment condition until ready for installation. Avoid ground contact or continuous exposure to moisture and direct sunlight. Some skinning and direct coloration of the insulation edges is normal if exposed to UV light prior to installation; however, it does not affect the performance of the panel. Some cupping of the panel is expected during shipment and can be rectified during installation by beginning installation from the center of the panel and working outward per the fastener standard of the designed application.

Explore our other ArmorWall Solutions:



BOARD SIZING AND INSULATING FACTORS

Board Coverage	Total Board Thickness	Sheathing Thickness	Insulation Thickness	R-Value	Weight ¹	SKU#
48"x96" (32sqft/sheet)	2"	1/2"	11/2"	R10	92 lbs	ANP200096
48"x120" (40sqft/sheet)	2"	1/2"	11/2"	R10	115 lbs	ANP200120
48"x96" (32sqft/sheet)	2 3/4"	1/2"	21/4"	R15	96 lbs	ANP234096
48"x120" (40sqft/sheet)	2 3/4"	1/2"	21/4"	R15	120 lbs	ANP234120
48"x96" (32sqft/sheet)	3 3/4"	1/2"	31/4"	R21	103 lbs	ANP334096
48"x120" (40sqft/sheet)	3 3/4"	1/2"	31/4"	R21	129 lbs	ANP334120

¹ Average board weight may vary based upon environmental conditions.

AIR / WATER / FIRE / THERMAL / FASTENER PROPERTIES

Air Leakage Resistance	Pass	ASTM E2357
Air Infiltration at 75 Pa	0.01 cfm/ft ² (0.1 L/s/m ²)	ASTM E283
Air Infiltration at 300 Pa	0.04 cfm/ft ² (0.2 L/s/m ²)	ASTM E283
Water Penetration at 6.27 psf (300 Pa)	Pass	ASTM E331 ¹
Mold and Mildew	no observed growth	ASTM C1338
Fastener Sealability ²	Pass	ASTM D1970
Fire Resistance	Pass	NFPA 285 ³
Vapor Permeance	0.18 Perms @ 10 mils (grains/hr in Hg ft ²) ⁴	ASTM E96 (Method A)
Flame Spread/Smoke Developed Index	<25 / <450	ASTM E84
Thermal Resistance	6.53 per inch	ASTM C518
Fastener Withdrawal Capacity	388.3 lbs	ASTM D1037 ⁵
Fastener Pull Through	505.2 lbs	ASTM D1037 ⁵
Fastener Shear in Sheathing Only	585.5 lbs	ASTM D1037 ⁵

¹ Total test duration full two continuous hours.

² ArmorWall NP is self-healing around cladding attachment fasteners.

³ ArmorWall NP passes NFPA 285 attached directly to the stud framing allowing any non-combustible veneer installed to its exterior as inclusive to the NFPA 285 approved assembly.

⁴ Permeability applies to only the coating.

⁵ Average ultimate value provided.

SHEAR PROPERTIES^{1,2}

Fastener Type	Min. Fastener Penetration into Framing	Panel Applied Direct to Framing (Fastener spacing at Panel Edges in Inches)			Panel Applied Direct to Framing w/ 1/2" Gypsum on Opposite Face (Fastener spacing at Panel Edges in Inches)		
		Shear (lbs/ft) w/ Framing of Douglas-Fir-Larch or Southern Pine					
		12"	6"	4"	6"		
#14-13	1"	301	437.5	537.5	570		

¹ Per ASTM E72 and comparable to table Z306.4.1 of the IBC.

² Data presented is average values of the test.

DEFLECTION PROPERTIES

	Test Method ¹	Stud Thickness	Span	Results
L/240	TAS 202-94	18 ga	86"	+113/-95 psf (+5400/-4560 Pa)
L/360	TAS 202-94	18 ga	86"	+113/-75 psf (+5400/-3600 Pa)
L/240	TAS 202-94	20 ga	86"	+60/-40 psf (+2880/-1920 Pa)
L/360	TAS 202-94	20 ga	86"	+60/-25 psf (+2880/-1200 Pa)
	TAS 203-94 ²	18 ga		+113/-95 psf (+5400/-4560 Pa)
	TAS 203-94 ²	20 ga		+60/-40 psf (+2880/-1920 Pa)

¹ Impact and Non-impact Resistance Building Envelope Components Using Uniform Static Air Pressure per Florida Building Code 6th Edition (2017) Section 1604.

² Criteria for Testing Products Subject to Cyclic Wind Pressure Loading per Florida Building Code 6th Edition (2017) Section 1604.



For specific inquiries regarding installation of ArmorWall please contact MaxLife Industries Customer Services.

Company Address | 4995 South Main Street, Salisbury, North Carolina 28147
 Website Address | www.maxlifeindustries.com
 Toll Free Number | 1-844-MAX4YOU (1-844-629-4968)
 Customer Service Email | cs@maxlifeindustries.com

