



- 1: (3) #10-9 ULP Gimlet Point Self-tapping Screws Per One-Brick IQBrick™ Panel
- 2: (6) #10-9 ULP Gimlet Point Self-tapping Screws Per Full IQBrick™ Panel
- 3: (6) #10-9 ULP Gimlet Point Self-tapping Screws Per Two-Brick IQBrick™ Panel



704-636-2411  
www.maxlifeindustries.com

Mail To:  
MaxLife Industries  
P.O. Box 2128  
Salisbury, NC 28145

**MAXLIFE**  
INDUSTRIES  
INNOVATING THE  
BUILDING ENCLOSURE

Ship To:  
1225 Chuck Taylor Lane  
Salisbury, North Carolina 28147

DETAIL:  
IQBRICK™ STANDARD FASTENING PATTERN

SCALE:  
NTS

REVISION:  
01

NOTES:

- RECOMMENDED FASTENER LOCATION AT LEAST ONE-HALF BRICK INTO THE PANEL
- DO NOT USE IMPACT DRIVERS
- USE 2,500 RPM MAX VARIABLE SPEED SCREW DRIVERS W/ TORQUE CONTROL OR A DEPTH SENSING NOSEPIECE
- IF THE IQBRICK™ PANEL IS CUT TO ONE FULL BRICK OR LESS (8" OR LESS) AT THE MOST NARROW PART ONLY (3) SCREWS ARE NECESSARY, ALTERNATIVELY A PANEL 8" OR GREATER REQUIRES (6)