



MAXLIFE
INDUSTRIES
INNOVATING THE
BUILDING ENCLOSURE

ArmorSeal

Sealants, Coatings, Tapes & Fasteners

SELF-ADHERED FLASHING

PRODUCT DESCRIPTION

ArmorSeal Self-Adhered Flashing is a puncture resistant water resistive barrier flashing used within the ArmorWall system in above-grade applications to detail large prefabricated panel assembly seams and differing substrates while maintaining extended UV exposure. The high UV resistance suits open cladding systems where maintaining protection is critical.

PRODUCT ADVANTAGES

ArmorSeal Self-Adhered Flashing is specifically used within the ArmorWall Fire-Rated Structural Insulated Sheathing™ system for its versatility, consistent properties resulting in high performance, and simple installation. The split paper release and pressure-sensitive adhesive on the reverse side allow this omni directional product to install quickly. The self-healing properties and durability help provide the air and water tightness necessary when detailing laps, seams, and transitions.

SEALANT PACKAGING AND CHARACTERISTICS	
4" Self-Adhered Flashing	SKU # SLFT06102
Size	4" x 65'-7" (60mm x 20m)
Packaging	6 Rolls per Case
9" Self-Adhered Flashing	SKU # SLFT09102
Size	9" x 65'-7" (230mm x 20m)
Packaging	2 Rolls per Case

PRODUCT LIMITATIONS

- Cover within 12 months of installation.
- Open joint gap not to exceed 2" (5.1 cm).
- Minimum 20°F (-6°C) and rising recommended application temperature.
- Replace membrane if subjected to asphaltic materials, chemicals, surfactants, or cleaning compounds which may effect water resistance of the membrane.
- For use above grade only.
- To ensure proper adhesion, ArmorSeal Self-Adhered Flashing should be pressure rolled to the ArmorWall panel surface immediately after application and in all directions.

HANDLING AND USE

Store rolls out of direct sunlight, out of inclement weather conditions, and on end in original packaging until ready for use. Ensure surface is sound, dry, and free from any adhesion impairing surface contaminants prior to application. ArmorSeal Self-Adhered Flashing does not require specialized tools or protective equipment and gear. All overlaps to be a minimum of 3" (8 cm) on vertical and horizontal seams. Use a pressure roller to ensure firm adhesion and to alleviate fishmouths. Top edges of all horizontally installed tape must be sealed with ArmorSeal Sealant immediately after application. Other seams can be sealed as desired per project specifications.

Explore our other ArmorWall System Components:

ArmorBoard	ArmorSeal Plus Coating	ArmorSeal BG Sealant
ArmorBoard Plus	ArmorSeal Sealant	ArmorSeal BG Self-Adhered Flashing
ArmorBoard Returns	ArmorSeal Mesh Reinforcement	ArmorSeal BG Mesh Reinforcement
ArmorBoard BG Return	ArmorSeal Self-Adhered Flashing	



For specific inquiries regarding installation please contact MaxLife Industries Customer Service.

Company Address | 4995 South Main Street, Salisbury, North Carolina 28147
 Website Address | www.maxlifeindustries.com
 Toll Free Number | 1-844-MAX4YOU (1-844-629-4968)
 Customer Service Email | cs@maxlifeindustries.com