



- 1: Metal Stud Frame
- 2: Concrete Slab Foundation
- 3: ArmorWall Plus Structural Insulated Sheathing (R10, R15, or R21 Standard) Starts Minimum 6" Above Grade
- 4: ArmorWall Below Grade (BG) (R10, R15, or R21 Standard)
- 5: #14-13 Self Tapping Screw
- 6: ArmorSeal Sealant (Gunnable Grade) at all Seams and Fasteners
- 7: Dimple Board Attached with Spray Adhesive
- 8: ArmorSeal Self-Adhered Flashing
- 9: Strip Drain
- 10: Foundation Waterproofing 12" Up Foundation Footing



1-844-MAX4YOU
 (1-844-629-4968)
www.maxlifeindustries.com

Mail To:
 MaxLife Industries
 P.O. Box 2128
 Salisbury, NC 28145

Ship To:
 4995 South Main Street
 Salisbury, North Carolina 28147

MAXLIFE
 INDUSTRIES
 INNOVATING THE
 BUILDING ENCLOSURE

DETAIL TITLE:
 ARMORWALL PLUS TO METAL STUD FRAME BASE OF
 WALL - TRANSITION TO ARMORWALL BELOW GRADE

DETAIL NO.:

SCALE:
 NTS

REVISION:
 01

NOTES:

- ARMORWALL BG IS MANUFACTURED WITH RETURNS ON THE TOP AND BOTTOM SIDES OF THE HORIZONTAL INSTALLATION ONLY PANEL. THE RESULT IS NO LONGER REQUIRING ATTACHMENT OF A ARMORBOARD PLUS END CAP AT THE BASE OF THE ARMORWALL PLUS PANEL SUCH AS IN THE TYPICAL INSTALLATION.
- VERY HEAVY TERMITE ZONES MAY REQUIRE A TERMITE SHIELD.