



- 1: Metal Stud Frame
- 2: Concrete Slab Foundation
- 3: ArmorWall Plus Structural Insulated Sheathing (R10, R15, or R21 Standard) Starts Minimum 6" Above Grade
- 4: Field-Adhered ArmorBoard Plus End Cap
- 5: Below Grade Insulation
- 6: #14-13 Self Tapping Screw
- 7: ArmorSeal Sealant (Gunnable Grade) at all Seams and Fasteners
- 8: Foundation Waterproofing



1-844-MAX4YOU  
 (1-844-629-4968)  
[www.maxlifeindustries.com](http://www.maxlifeindustries.com)

Mail To:  
 MaxLife Industries  
 P.O. Box 2128  
 Salisbury, NC 28145

**MAXLIFE**  
 INDUSTRIES  
 INNOVATING THE  
 BUILDING ENCLOSURE

Ship To:  
 4995 South Main Street  
 Salisbury, North Carolina 28147

DETAIL TITLE:  
 ARMORWALL PLUS TO METAL STUD FRAME BASE OF  
 WALL - TRANSITION TO BELOW GRADE INSULATION

DETAIL NO.:

SCALE:  
 NTS

REVISION:  
 01

NOTES:  
 - VERY HEAVY TERMITE ZONES MAY REQUIRE A TERMITE SHIELD.