



- 1: Metal Stud Frame
- 2: ArmorWall Plus Structural Insulated Sheathing (R10, R15, or R21 Standard)
- 3: #14-13 Self Tapping Screw
- 4: ArmorSeal Sealant (Gunnable Grade) at all Seams and Fasteners
- 5: Fire Retardant Treated Blocking at Full Depth of Exterior Wall Assembly Around Entire Opening
- 6: Approved Self-Adhered Membrane WRB at Full Depth of Punched Opening and Minimum 4" on Face of ArmorWall
- 7: Bead of ArmorSeal Sealant (Gunnable Grade) on Outer Perimeter Edge of Self-Adhered WRB



1-844-MAX4YOU
 (1-844-629-4968)
www.maxlifeindustries.com

Mail To:
 MaxLife Industries
 P.O. Box 2128
 Salisbury, NC 28145

MAXLIFE
 INDUSTRIES
 INNOVATING THE
 BUILDING ENCLOSURE

Ship To:
 4995 South Main Street
 Salisbury, North Carolina 28147

DETAIL TITLE:
 ARMORWALL PLUS TO METAL STUD FRAME WINDOW
 PUNCHED OPENING - FRT BLOCKING RETURN

DETAIL NO.:

SCALE:

NTS

REVISION:

01

NOTES: