



Vertical Installation Standard  
Fastener Position Symbol



Horizontal Installation Standard  
Fastener Position Symbol



Vertical and Horizontal Shared  
Installation Standard Fastener  
Position Symbol



1-844-MAX4YOU  
(1-844-629-4968)  
www.maxlifeindustries.com

Mail To:  
MaxLife Industries  
P.O. Box 2128  
Salisbury, NC 28145

Ship To:  
4995 South Main Street  
Salisbury, North Carolina 28147

**MAXLIFE**  
INDUSTRIES  
INNOVATING THE  
BUILDING ENCLOSURE

DETAIL:  
ARMORWALL HORIZONTAL INSTALLATION FASTENING PATTERN

NOTES:  
- STANDARD FASTENING PATTERN IS 12" O.C. INTO EACH STUD VERTICALLY AND 12" O.C. AROUND THE PERIMETER. FOR INCREASED SHEAR VALUES, THE PERIMETER IS INCREASED TO EITHER 6" O.C. OR 4" O.C., WHICHEVER VALUES IS DESIRED. SEE THE PRODUCT DATA SHEET FOR DESIGN VALUES.  
- IF USING FOR SHEAR, ALL PERIMETER EDGES OF THE PANEL SHOULD BE BLOCKED

SCALE:  
NTS

REVISION:  
01